

3M 2393 Premium High Temperature Masking Tape

Category: Polymer, Adhesive

Material Notes:

3M™ Masking Tape 2393 is a smooth, heavy duty, mini-crepe, premium high temperature masking tape. It is specifically designed for those applications where easy removal after bake is important. This masking tape offers excellent paint mask performance with high solids paints and clear coats used in the transportation industry.Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-2393-Premium-High-Temperature-Masking-Tape.php

Physical Properties	Metric	English	Comments
Thickness	4.70 microns	0.185 mil	ASTM D3652

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	26.5 MPa	3840 psi	ASTM D3759
Elongation at Break	11 %	11 %	ASTM D3759
Peel Strength	0.351 kN/m	2.00 pli	to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	163 °C	325 °F	for 30 mins

Descriptive Properties	Value	Comments
Adhesive Type	Rubber	
Appearance	Tan	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China