

3M 3320 HVAC Construction

Category : Metal , Nonferrous Metal , Aluminum Alloy , Polymer , Tape

Material Notes:

Aluminum foil/scrim/laminate. UL 723 Classified. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-3320-HVAC-Construction.php

Physical Properties	Metric	English	Comments
Thickness	152 microns	6.00 mil	Backing; ASTM D3652
	170 microns	6.70 mil	Total; ASTM D3652

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	41.9 MPa	6080 psi	ASTM D3759
Peel Strength	0.88746 kN/m	5.0625 pli	Adhesion to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	79.0 °C	174 °F	
Minimum Service Temperature, Air	-29.0 °C	-20.2 °F	

Descriptive Properties	Value	Comments
Adhesive Type	Acrylic	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China