

## 3M 3340 HVAC Construction

Category : Metal , Nonferrous Metal , Aluminum Alloy , Polymer , Tape

**Material Notes:**

Aluminum foil tape, for use with rigid and flexible ducts. UL 181 A-P and 181 B-FX Listed. Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-3340-HVAC-Construction.php](http://www.lookpolymers.com/polymer_3M-3340-HVAC-Construction.php)

Physical Properties	Metric	English	Comments
Thickness	50.8 microns	2.00 mil	Backing; ASTM D3652
	102 microns	4.00 mil	Total; ASTM D3652

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	34.3 MPa	4970 psi	ASTM D3759
Peel Strength	0.3287 kN/m	1.875 pli	Adhesion to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	121 °C	250 °F	
Minimum Service Temperature, Air	-34.0 °C	-29.2 °F	

Descriptive Properties	Value	Comments
Adhesive Type	Acrylic	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China