

## 3M 34201 Lead Foil Tape

Category : Metal , Nonferrous Metal , Lead Alloy , Polymer , Tape

**Material Notes:**

Removable rubber adhesive Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-34201-Lead-Foil-Tape.php](http://www.lookpolymers.com/polymer_3M-34201-Lead-Foil-Tape.php)

Physical Properties	Metric	English	Comments
Thickness	127 microns	5.00 mil	Backing; ASTM D3652
	159 microns	6.25 mil	Total; ASTM D3652

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	22.0 MPa	3190 psi	ASTM D3759
Peel Strength	0.5478 kN/m	3.125 pli	Adhesion to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	82.0 °C	180 °F	
Minimum Service Temperature, Air	-18.0 °C	-0.400 °F	

Descriptive Properties	Value	Comments
Adhesive Type	Rubber	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China