

3M 4104 Single-Coated Foam Tape

Category : Polymer , Tape

Material Notes:

3M™ Single-Coated Foam Tapes will adhere to a variety of substrates, including latex-painted wood, lacquered wood, enameled steel, glass, aluminum, stainless steel, acrylic, ABS, and PVC (non-plasticized) as tape adhesion is typically satisfactory within 20 minutes and continues to build and additional time. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-4104-Single-Coated-Foam-Tape.php

Physical Properties	Metric	English	Comments
Density	0.192 g/cc	0.00694 lb/in ³	foam with adhesive; ASTM D3574
Thickness	76.2 microns	3.00 mil	Release Liner
	6350 microns	250 mil	Total

Mechanical Properties	Metric	English	Comments
Hardness, Shore OO	75	75	Foam with adhesive; ASTM D2240
Tensile Strength at Break	0.795 MPa	115 psi	Die "A"; ASTM D3759
Elongation at Break	100 %	100 %	Die "A"; ASTM D3759
Compressive Strength	0.0276 MPa	4.00 psi	Deflection, Compress 25%; ASTM D3574
Compression Set	8.0 %	8.0 %	ASTM D1667

Thermal Properties	Metric	English	Comments
Thermal Conductivity	0.0660 W/m-K	0.458 BTU-in/hr-ft ² -°F	ASTM C518

Electrical Properties	Metric	English	Comments
Surface Resistivity per Square	1.00e+15 ohm	1.00e+15 ohm	Non-adhesive side; ASTM D257
	1.00e+15 ohm	1.00e+15 ohm	Adhesive side; ASTM D257
Dielectric Strength	1.97 kV/mm	50.0 kV/in	ASTM D149

Descriptive Properties	Value	Comments
Adhesive Type	350	
Appearance	Natural-white	
		liner

Descriptive Properties	White Value	Comments
------------------------	-------------	----------

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com
Email : sales@lookpolymers.com
Tel : +86 021-51131842
Mobile : +86 13061808058
Skype : lookpolymers
Address : United North Road 215,Fengxian District, Shanghai City,China