

## 3M 465 Splicing Tapes

Category : Polymer , Adhesive

**Material Notes:**

3M™ Splicing Tapes utilize on acrylic pressure sensitive adhesive system that offers a balance of initial adhesion and good holding power. Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-465-Splicing-Tapes.php](http://www.lookpolymers.com/polymer_3M-465-Splicing-Tapes.php)

Physical Properties	Metric	English	Comments
Thickness	50.8 microns	2.00 mil	Tape
	102 microns	4.00 mil	Release Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.27391 kN/m	1.5625 pli	Adhesion to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	82.0 °C	180 °F	Short term
	121 °C	250 °F	Long term

Descriptive Properties	Value	Comments
Adhesive Type	400	
Appearance	Clear	
Liner	Tan 60# Densified Kraft	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China