

3M 6146 Kraft Medium Duty Reinforced Water Activated Tape

Category: Polymer, Adhesive

Material Notes:

3M™ Medium Duty Reinforced Water Activated Tape 6146 Kraft is used for box sealing and other packaging applications. This product has a fiberglass reinforced paper backing and high tack water activated adhesive system.Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-6146-Kraft-Medium-Duty-Reinforced-Water-Activated-Tape.php

| Physical Properties | Metric | English | Comments |
|---------------------|-------------|----------|--------------------|
| Thickness | 165 microns | 6.50 mil | Caliper; ASTM D645 |

| Mechanical Properties | Metric | English | Comments |
|------------------------------------|-----------------|-----------------|----------|
| Film Tensile Strength at Break, MD | 63.6 - 68.9 MPa | 9220 - 9990 psi | |
| Film Tensile Strength at Break, TD | 26.5 - 31.8 MPa | 3840 - 4610 psi | |

| Descriptive Properties | Value | Comments |
|------------------------|--|----------|
| Adhesive Type | High Tack, Water Activated, modified Starch Based Adhesive | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China