

3M 6147 Performance Reinforced Water Activated Tape

Category : Polymer , Adhesive

Material Notes:

3M™ Performance Reinforced Water Activated Tape 6147 is used for box sealing and other packaging applications. This has a fiberglass reinforced paper backing and a high tack water activated adhesive system. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-6147-Performance-Reinforced-Water-Activated-Tape.php

Physical Properties	Metric	English	Comments
pH	4.5 - 6.0	4.5 - 6.0	
Thickness	216 microns	8.50 mil	ASTM D645

Mechanical Properties	Metric	English	Comments
Film Tensile Strength at Break, MD	48.7 - 52.7 MPa	7060 - 7640 psi	
Film Tensile Strength at Break, TD	20.3 - 24.3 MPa	2940 - 3520 psi	

Descriptive Properties	Value	Comments
Adhesive Type	High Tack, Water Activated, modified Starch Based Adhesive	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China