

3M 9437 Adhesive Transfer Tape with Adhesive 100MP

Category : Polymer , Adhesive

Material Notes:

3M™ Adhesive Transfer Tape 9437 with 3M™ Adhesive 100MP is designed for harsh environments such as automotive, aerospace and outdoor applications. Features: Excellent temperature and chemical resistance. Exceptional shear holding strength at elevated temperatures. Strong bond to metals and high surface energy plastics (e.g. ABS, polycarbonate). Polyester liner provides excellent die-cutting surface. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-9437-Adhesive-Transfer-Tape-with-Adhesive-100MP.php

Physical Properties	Metric	English	Comments
Thickness	50.8 microns	2.00 mil	

Mechanical Properties	Metric	English	Comments
Peel Strength	0.18626 kN/m	1.0625 pli	Polypropylene, 72 Hour Dwell, (90° peel, 12"/min.) on 2 mil aluminum; ASTM D3330
	0.51494 kN/m	2.9375 pli	Polycarbonate, 72 Hour Dwell, (90° peel, 12"/min.) on 2 mil aluminum; ASTM D3330
	0.526 kN/m	3.00 pli	Stainless Steel, 20 Minute Dwell, (90° peel, 12"/min.) on 2 mil aluminum; ASTM D3330
	0.79981 kN/m	4.5625 pli	Stainless Steel, 72 Hour Dwell, (90° peel, 12"/min.) on 2 mil aluminum; ASTM D3330
	1.3695 kN/m	7.8125 pli	Stainless Steel, Ultimate Bond, (90° peel, 12"/min.) on 2 mil aluminum; ASTM D3330

Processing Properties	Metric	English	Comments
Shelf Life	12.0 Month	12.0 Month	

Descriptive Properties	Value	Comments
Adhesive Type	100MP	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China