

## 3M 9499 Splicing Tape

Category : Polymer , Adhesive

**Material Notes:**

3M™ Splicing Tapes utilize an acrylic pressure sensitive adhesive system that offers a balance of initial adhesion and good holding power. Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-9499-Splicing-Tape.php](http://www.lookpolymers.com/polymer_3M-9499-Splicing-Tape.php)

Physical Properties	Metric	English	Comments
Thickness	50.8 microns	2.00 mil	Tape Only
	76.2 microns	3.00 mil	Release Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.49303 kN/m	2.8125 pli	to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	149 °C	300 °F	Long term
	260 °C	500 °F	Short term

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Adhesive Carrier	None	
Adhesive Type	430	
Appearance	Light Red	
Liner	Tan 60# Densified Kraft	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China