

## 3M 9738 Double Coated Splicing Tape

Category : Polymer , Adhesive

**Material Notes:**

3M™ Double Coated Tape 9737 is a Clear 3.5 mil acrylic double coated tape on a polyester film carrier. Features: High tack, acrylic adhesive offers good low and elevated temperature resistance. Adheres well to both kraft and coated papers. High performance splicing tape for use on paper, plastics and other continuous web processes. Electronics, General Industrial, Appliances, Medical Devices, Power Tools, Automotive, Transportation, Aircraft, Airplane. Adhering, joining, affixing, bonding, mounting, holding, laminating, and attaching. Information provided by 3M

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-9738-Double-Coated-Splicing-Tape.php](http://www.lookpolymers.com/polymer_3M-9738-Double-Coated-Splicing-Tape.php)

| Physical Properties | Metric       | English  | Comments |
|---------------------|--------------|----------|----------|
| Thickness           | 33.0 microns | 1.30 mil | Carrier  |
|                     | 81.3 microns | 3.20 mil | Liner    |
|                     | 109 microns  | 4.30 mil | Tape     |

| Mechanical Properties | Metric     | English  | Comments                |
|-----------------------|------------|----------|-------------------------|
| Peel Strength         | 0.657 kN/m | 3.75 pli | to Steel, Initial at RT |

| Thermal Properties               | Metric   | English  | Comments   |
|----------------------------------|----------|----------|------------|
| Maximum Service Temperature, Air | 127 °C   | 261 °F   | Long term  |
|                                  | 149 °C   | 300 °F   | Short term |
| Minimum Service Temperature, Air | -23.0 °C | -9.40 °F |            |

| Processing Properties | Metric     | English    | Comments |
|-----------------------|------------|------------|----------|
| Shelf Life            | 12.0 Month | 12.0 Month |          |

| Descriptive Properties | Value                            | Comments |
|------------------------|----------------------------------|----------|
| Appearance             | Clear                            |          |
| Liner                  | 55# Densified Kraft Paper, White |          |

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China