

3M Controltac™ IJ160C Graphic Film with Comply™ Adhesive

Category : Polymer , Film

Material Notes:

4-mil, opaque white, vinyl film with a matte finish; Pressure-activated adhesive for easy sliding, tacking, snap up and repositioning; Film IJ160C-10 also has Comply™ Adhesive air release channels for fast, easy, bubble-free graphic installations; Excellent hiding power and Removable with heat Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Controltac-IJ160C-Graphic-Film-with-Comply-Adhesive.php

Physical Properties	Metric	English	Comments
Thickness	102 microns	4.00 mil	without adhesive
	114 - 127 microns	4.50 - 5.00 mil	with adhesive

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	22.5 MPa	3260 psi	
Peel Strength	0.158 kN/m	0.900 pli	Adhesion to Fruehauf pre-painted panels
	0.578 kN/m	3.30 pli	Adhesion to ABS

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	38.0 °C	100 °F	
Minimum Service Temperature, Air	4.40 °C	39.9 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China