

## 3M Dyneon™ FX 5920A Polymer Processing Additive

Category : Other Engineering Material , Additive/Filler for Polymer , Polymer , Thermoset , Fluoropolymer, TS

### Material Notes:

Dynamar FX 5902A is a free-flowing fluoropolymer based processing additive that is designed for use at very low levels to improve processing of thermoplastics. At the very low use levels (typically 200-1000 ppm) necessary to improve processing, it does not alter or detract from good physical properties associated with high strength plastics. Features and Benefits Broadens extrusion processing capabilities of polyolefin resins Ideal for use in polyolefin resins containing antiblocking agents, pigments, and other inorganic additives Reduces or eliminates die build-up Lowers apparent melt viscosity For use at very low levels Free-flowing fluoropolymer based processing aid Can offer performance and cost advantages Information provided by Dyneon, A 3M Company

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-Dyneon-FX-5920A-Polymer-Processing-Additive.php](http://www.lookpolymers.com/polymer_3M-Dyneon-FX-5920A-Polymer-Processing-Additive.php)

Physical Properties	Metric	English	Comments
Bulk Density	0.700 g/cc	0.0253 lb/in <sup>3</sup>	
Particle Mesh Size	<= 10 Mesh	<= 10 Mesh	

Descriptive Properties	Value	Comments
Active Ingredients (%)	97	
Color	White to off-white	
Form	Granular	
Inorganic Additives %	3	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China