

3M FA102 Destructible Acetate Label Products

Category : Polymer , Adhesive

Material Notes:

3M™ Destructible Acetate Label Products FA102 and FA112 offer consistent, high quality film that fractures when attempting label removal from many surfaces. These acetate labels utilize 3M™ Adhesive P1212, which is a high clarity general purpose acrylic emulsion for use on overlamination and decorative films that exhibits good initial tack, excellent die cutting properties, minimal cold flow, and good UV resistance. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-FA102-Destructible-Acetate-Label-Products.php

Physical Properties	Metric	English	Comments
Thickness	50.8 microns	2.00 mil	Facestock
	78.7 microns	3.10 mil	Liner

Mechanical Properties	Metric	English	Comments
Peel Strength	0.526 kN/m	3.00 pli	180° Peel, 12"/min., 1" wide sample; TLMI Method

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	49.0 °C	120 °F	Application
	60.0 °C	140 °F	Service
Minimum Service Temperature, Air	-29.0 °C	-20.2 °F	Service
	5.00 °C	41.0 °F	Application

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Adhesive Type	P1212 Perm 18	
Liner	50# SC	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China