

3M Hi-Strength 94 ET Cylinder Spray Adhesive

Category : Polymer , Adhesive

Material Notes:

A high performance, industrial grade spray adhesive with a unique low telegraphing pebble spray pattern. Features: Bonds to a variety of substrates including decorative laminate, headliners, and soft foams. Typically used in woodworking and specialty vehicle applications, especially when VOC's are a concern. Extended tack allows for longer bonding range. Features a low telegraphing spray pattern. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Hi-Strength-94-ET-Cylinder-Spray-Adhesive.php

Physical Properties	Metric	English	Comments
Density	0.935 g/cc	0.0338 lb/in ³	
Solids Content	25 %	25 %	
Volatile Organic Compounds (VOC) Content	<= 80 g/l	<= 80 g/l	

Descriptive Properties	Value	Comments
Appearance	Translucent and Red	
Base	Synthetic Elastomer	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China