

## 3M Jet-Weld™ TE-030 Adhesive

Category : Polymer , Adhesive , Thermoset , Polyurethane, TS , Thermoset Polyurethane, Adhesive

### Material Notes:

A warm applied, moisture-curing polyurethane adhesive for wood working, laminating and plastic component assembly. Extrudable grade with fast set time ideal for bonding wood. Can bond selected plastics. The color is white/off white. The open time is 1 minute, and the set time is 30 seconds. Information provided by 3M Adhesives Division.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_3M-Jet-Weld-TE-030-Adhesive.php](http://www.lookpolymers.com/polymer_3M-Jet-Weld-TE-030-Adhesive.php)

Physical Properties	Metric	English	Comments
Viscosity	16000 cP	16000 cP	

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	60	60	
Tensile Strength, Ultimate	26.2 MPa	3800 psi	
Elongation at Break	725 %	725 %	
Modulus of Elasticity	0.0800 GPa	11.6 ksi	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	121 °C	250 °F	

Processing Properties	Metric	English	Comments
Processing Temperature	121 °C	250 °F	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China