

3M Scotch® 232 High Performance Masking Tape

Category : Polymer , Adhesive

Material Notes:

Scotch® High Performance Masking Tape 232 is designed to be used in medium temperature paint bake operations. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Scotch-232-High-Performance-Masking-Tape.php

Physical Properties	Metric	English	Comments
Thickness	4.06 microns	0.160 mil	ASTM D3652

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	29.5 MPa	4280 psi	ASTM D3759
Elongation at Break	8.0 %	8.0 %	ASTM D3759
Peel Strength	0.29582 kN/m	1.6875 pli	to Steel; ASTM D3330

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	121 °C	250 °F	for 30 mins

Descriptive Properties	Value	Comments
Adhesive Type	Rubber	
Appearance	Tan	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China