

3M Scotchkote™ 165CS Urethane Sealer

Category: Polymer, Thermoset, Polyurethane, TS, Thermoset Polyurethane, Liquid

Material Notes:

Scotchkote Urethane Sealer 165CS has been specifically developed as a low viscosity primer/sealer for concrete and cementitious surfaces prior to application of other Scotchkote urethane systems. Product Features: Combines good application characteristics with excellent penetration and adhesion Designed for application by brush or roller Designed for use on concrete surfaces but can be used on other porous mineral substrates. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Scotchkote-165CS-Urethane-Sealer.php

| Physical Properties | Metric | English | Comments |
|---------------------|-------------|---------------|----------|
| Density | 1.10 g/cc | 0.0397 lb/in³ | |
| Solids Content | 100 % | 100 % | |
| Thickness | 102 microns | 4.00 mil | |

| Processing Properties | Metric | English | Comments |
|-----------------------|---------------|------------------|---------------|
| Cure Time | 180 min | 3.00 hour | Hard Dry |
| | 300 - 360 min | 5.00 - 6.00 hour | Full Hardness |
| | 10100 min | 168 hour | Full Cure |

| Descriptive Properties | Value | Comments |
|------------------------|-------------------|----------|
| Appearance | Translucent Brown | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China