

3M Scotchkote™ 412 Fusion Bonded Epoxy Coating

Category: Polymer, Thermoset, Epoxy

Material Notes:

3M Scotchkote Fusion Bonded Epoxy Coating 413 is a one-part, heat curable, thermosetting epoxy coating designed for corrosion protection of reinforcing steel. The epoxy is applied to preheated steel as a dry powder which melts and cures to a uniform coating thickness. This bonding process provides excellent adhesion and coverage on concrete reinforcing bar, wire fabric, piling, tensioning hardware and other steel member of any size or shape. Scotchkote 413 is resistant to corrosive agents such as deicing salts, airborne slat spray, sea water, harsh chemicals, acid rain, carbonation, contaminated aggregate and concrete additives. Information provided by 3M

Order this product through the following link:

http://www.lookpolymers.com/polymer_3M-Scotchkote-412-Fusion-Bonded-Epoxy-Coating.php

Physical Properties	Metric	English	Comments
Density	1.21 g/cc	0.0437 lb/in ³	

Mechanical Properties	Metric	English	Comments
Hardness, Knoop	>= 16	>= 16	
Impact Test	9.04 J	6.67 ft-lb	ASTM A775
	18.1 J	13.3 ft-lb	0.32cm x 7.6cm x 7.6cm steel panel, 1.6cm radius tup; ASTM G14
Penetration	0.00	0.00	ASTM G17
	@Temperature -40.0 - 116 °C	@Temperature -40.0 - 241 °F	
Abrasion	17	17	[mg] CS-17, 1000 cycles, 1000g; ASTM D775

Processing Properties	Metric	English	Comments
Gel Time	0.066666 - Error in fixSigDigits: @digits must be between 1 and 12. @digits is: 15 min	0.066666 - Error in fixSigDigits: @digits must be between 1 and 12. @digits is: 15 min	
	@Temperature 232 °C	@Temperature 450 °F	
	0.100 - 0.150 min	0.100 - 0.150 min	
	@Temperature 204 °C	@Temperature 399 °F	

Descriptive Properties	Value	Comments
Appearance	Green	



Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China