

## A. Schulman POLYFORT™ FPP 1200H High Flow, Calcium Carbonate Fortified Homopolymer Polypropylene

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene with 40% Calcium Carbonate (CaCO3) Filler

### Material Notes:

Description Polyfort® FPP 1200H is a high flow 40% calcium carbonate fortified homopolymer polypropylene. Information provided by A. Schulman.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_A-Schulman-POLYFORT-FPP-1200H-High-Flow-Calcium-Carbonate-Fortified-Homopolymer-Polypropylene.php](http://www.lookpolymers.com/polymer_A-Schulman-POLYFORT-FPP-1200H-High-Flow-Calcium-Carbonate-Fortified-Homopolymer-Polypropylene.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.23 g/cc	1.23 g/cc	ASTM D792
Melt Flow	12 - 20 g/10 min	12 - 20 g/10 min	ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	98	98	ASTM D785
Tensile Strength, Yield	27.0 MPa	3920 psi	ASTM D638
Elongation at Break	2.0 %	2.0 %	ASTM D638
Flexural Modulus	2.618 GPa	379.7 ksi	ASTM D790
Izod Impact, Notched	0.407 J/cm	0.762 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	124 °C	255 °F	ASTM D648
Deflection Temperature at 1.8 MPa (264 psi)	88.0 °C	190 °F	ASTM D648

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China