

Alloy Wire International RW 118 Hot Cutting Wire - High Strength

Category : Metal

Material Notes:

Maintains high strength at elevated temperatures. Used for cutting expanded polystyrene (EPS) foam and for the heat sealing of polypropylene bags. Information provided by Alloywire International.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Alloy-Wire-International-RW-118-Hot-Cutting-Wire-High-Strength.php

Physical Properties	Metric	English	Comments
Density	8.18 g/cc	0.296 lb/in ³	

Thermal Properties	Metric	English	Comments
CTE, linear	12.7 $\mu\text{m}/\text{m}\cdot^\circ\text{C}$	7.06 $\mu\text{in}/\text{in}\cdot^\circ\text{F}$	
	@Temperature 20.0 - 100 °C	@Temperature 68.0 - 212 °F	
Melting Point	1370 °C	2500 °F	
Maximum Service Temperature, Air	300 °C	572 °F	

Electrical Properties	Metric	English	Comments
Electrical Resistivity	0.000118 ohm-cm	0.000118 ohm-cm	
	@Temperature 20.0 °C	@Temperature 68.0 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China