

American Polymers API 392 Polystyrene

Category : Polymer , Thermoplastic , Polystyrene (PS) , Polystyrene, Molded, Unreinforced

Material Notes:

API 392 is a general purpose polystyrene produced in pellet form for injection molding. API 392 has excellent clarity and high flow. Applications: Used in the manufacture of containers, housewares, toys and medical applications. Information provided by American Polymers, Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_American-Polymers-API-392-Polystyrene.php

Physical Properties	Metric	English	Comments
Density	1.05 g/cc	0.0379 lb/in ³	ASTM D792
Melt Flow	12 g/10 min	12 g/10 min	Condition G; ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell L	71	71	ASTM D785
Tensile Strength, Ultimate	42.7 MPa	6200 psi	ASTM D638
Elongation at Break	1.0 %	1.0 %	ASTM D638
Tensile Modulus	2.90 GPa	420 ksi	ASTM D638
Izod Impact, Notched	0.160 J/cm @Thickness 3.17 mm	0.300 ft-lb/in @Thickness 0.125 in	injection molded sample; ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	87.8 °C	190 °F	Annealed; ASTM D648
Vicat Softening Point	97.8 °C	208 °F	ASTM D1525

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China