

Aremco Pyro-Tape™ 682-DS High Temperature Tape Double sided, single layer, fiberglass tape with silicone adhesive

Category : Polymer , Adhesive , Tape

Material Notes:

Applications Double Sided Features Assembly of high temp components and films.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Aremco-Pyro-Tape-682-DS-High-Temperature-Tape-Double-sided-single-layer-fiberglass-tape-with-silicone-adhesive.php

| Physical Properties | Metric | English | Comments |
|---------------------|-------------|----------|----------|
| Thickness | 178 microns | 7.00 mil | |

| Thermal Properties | Metric | English | Comments |
|----------------------------------|----------|----------|----------|
| Maximum Service Temperature, Air | -73.0 °C | -99.4 °F | |
| | 260 °C | 500 °F | |

| Descriptive Properties | Value | Comments |
|------------------------|------------|----------|
| Adhesion | 25 oz/in | |
| Tape Tensile Strength | 175 lbs/in | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China