

## Arkema Group Lacovyl® PE 1312 PVC

Category: Polymer, Thermoplastic, Vinyl (PVC), PVC, Foam Grade

## **Material Notes:**

LACOVYL PE 1312 is a vinyl chloride homopolymer manufactured by emulsion polymerization process for the preparation of high viscosity plastisols. It is particularly suitable for the manufacture of compact or foam coatings containing high plasticizer levels.\* MAIN CHARACTERISTICS Viscosity index (ISO 1628-2):125 ml/g,(K value:70). \* APPLICATIONSLACOVYL PE 1312 may be used in the following areas: flexible coated fabrics, leather cloths, extrudable mastics for cars, resilient low density foams, and as thickening agent to change the rheology of a product. ISO data provided by the manufacturer, Arkema.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_Arkema-Group-Lacovyl-PE-1312-PVC.php

Physical Properties	Metric	English	Comments
Viscosity Test	125 cm³/g	125 cm³/g	Viscosity Number

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China