

Arkema Group Lacovyl® RB 8010 PVC

Category: Polymer, Thermoplastic, Vinyl (PVC), PVC, Molded

Material Notes:

LACOVYL RB 8010 is a low molecular weight vinyl chloride homopolymer produced by mass polymerization process using the Elf Atochem's latest technology. Its characteristics are: Viscosity index (ISO 1628-2):80 ml/g, (K value:57). Apparent density (ISO 60):0.62 g/ml. ease of fusion and good flow characteristics in the molten state facilitating low temperature processing. good porosity and high apparent density providing high productivity in compound mixers and extruders. high level of purity due to the mass polymerization process giving finished products of very good transparency. a narrow range of particle size distribution. * RECOMMENDED APPLICATIONS Provides finished products of high transparency, good gloss and free from fish eyes by: calendering and extrusion of rigid sheets and films. extrusion and injection blow-molding of bottles. Injection molding of rigid parts. Extrusion of small rigid profiles and monofilaments. Production of powder coatings by the fluidization method. Molding of gramophone records (Addition resin). * EXAMPLES OF APPLICATION NAKAN RMA 705 N NAKAN RMS 501 L NAKAN RRS 40 ISO data provided by the manufacturer, Arkema.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Arkema-Group-Lacovyl-RB-8010-PVC.php

Physical Properties	Metric	English	Comments
Viscosity Test	80 cm³/g	80 cm³/g	Viscosity Number

Optical Properties	Metric	English	Comments
Transmission, Visible	80 %	80 %	Mfr. reports 'Transparent' but doesn't quantify.

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China