

## Arkema Group Lacovyl® S 110 P PVC

Category: Polymer, Thermoplastic, Vinyl (PVC), PVC, Molded

## **Material Notes:**

LACOVYL S 110 P is a vinyl chloride homopolymer produced by a suspension polymerization process. Characteristics: Viscosity index (ISO 1628-2):112 ml/g, (K value:67). Apparent density (ISO 60):0.56 g/ml. molecular weight and morphology designed to give good processability with excellent mechanical properties. high tolerance of inorganic fillers in rigid PVC formulations. a very weak coloring of the resin after processing makes it possible to obtain profiles with regular color. \* RECOMMENDED APPLICATIONS Extrusion of rigid profiles with improved mechanical properties (window frame, fencing etc...). Sheet extrusion. Extrusion of rigid pipe for all applications: water adduction, drainage, sewerage, conduit. ISO data provided by the manufacturer, Arkema.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_Arkema-Group-Lacovyl-S-110-P-PVC.php

Physical Properties	Metric	English	Comments
Viscosity Test	112 cm³/g	112 cm³/g	Viscosity Number

## Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China