

Asahi Glass Fluon® LM-720AP LM-ETFE Fluororesin

Category : Polymer , Thermoplastic , Fluoropolymer , ETFE/ECTFE , Modified ETFE, Unreinforced

Material Notes:

Fluon®LM-ETFE combines the excellent properties in heat resistance and other mechanical properties owned by ETFE resin and the low melting point. Information provided by Asahi Glass Company, Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Asahi-Glass-Fluon-LM-720AP-LM-ETFE-Fluororesin.php

Physical Properties	Metric	English	Comments
Melt Flow	10 - 20 g/10 min	10 - 20 g/10 min	ASTM D359

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	43.0 MPa	6240 psi	ASTM D638
Elongation at Break	380 %	380 %	ASTM D638

Descriptive Properties	Value	Comments
Heat Ageing (retention of elongation)	120%	
Heat Ageing (retention of tensile strength)	90%	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China