

Ashley Polymers Ashlene® P1430 Polycarbonate, 30% Glass Reinforced

Category : Polymer , Thermoplastic , Polycarbonate (PC) , Polycarbonate, 30% Glass Filled

Material Notes:

A 30% glass reinforced polycarbonate for increased mechanical strength and thermal properties. P1433 with UV stabilizer. Data provided by the manufacturer

Order this product through the following link:

http://www.lookpolymers.com/polymer_Ashley-Polymers-Ashlene-P1430-Polycarbonate-30-Glass-Reinforced.php

Physical Properties	Metric	English	Comments
Density	1.43 g/cc	0.0517 lb/in ³	ASTM D792
Water Absorption	0.26 %	0.26 %	ASTM D570
Linear Mold Shrinkage	0.010 cm/cm	0.010 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	124 MPa	18000 psi	ATSM D638
Elongation at Break	4.0 %	4.0 %	ASTM D638
Flexural Modulus	7.20 GPa	1040 ksi	ASTM D790
Izod Impact, Notched	1.07 J/cm	2.00 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	151 °C	304 °F	ASTM D648
Deflection Temperature at 1.8 MPa (264 psi)	145 °C	293 °F	ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China