

## Ashley Polymers Ashlene® PE126WO PET Polyester, 30% Glass Reinforced

Category : Polymer , Thermoplastic , Polyester, TP , Polyethylene Terephthalate (PET) , Polyethylene Terephthalate (PET), Glass Fiber Filled, Flame Retardant

**Material Notes:**

PET Polyester with 30% glass reinforcement, flame retardant, natural. Note: Colors will modify properties.Data provided by the manufacturer

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Ashley-Polymers-Ashlene-PE126WO-PET-Polyester-30-Glass-Reinforced.php](http://www.lookpolymers.com/polymer_Ashley-Polymers-Ashlene-PE126WO-PET-Polyester-30-Glass-Reinforced.php)

Physical Properties	Metric	English	Comments
Density	1.68 g/cc	0.0607 lb/in <sup>3</sup>	ASTM D792
Linear Mold Shrinkage	0.0030 cm/cm	0.0030 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	131 MPa	19000 psi	ASTM D638
Elongation at Break	3.0 %	3.0 %	
Flexural Modulus	9.00 GPa	1310 ksi	ASTM D790
Izod Impact, Notched	0.690 J/cm	1.29 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Melting Point	254 °C	489 °F	ASTM D3418
Flammability, UL94	V-0	V-0	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China