

Axiall 10705 Wire & Cable Flexible PVC

Category: Polymer, Thermoplastic, Vinyl (PVC), PVC, Wire and Cable Grade

Material Notes:

Non-lead stabilized general purpose 75C compound with good low temperature properties. Formulated for increased line speed and reduced surface gloss.Information provided by Georgia GulfGeorgia Gulf became Axiall Corporation in 2013.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Axiall-10705-Wire-Cable-Flexible-PVC.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.28 - 1.32 g/cc	1.28 - 1.32 g/cc	ASTM D-792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	67 - 73	67 - 73	delayed; ASTM D-2240
Tensile Strength, Yield	9.51 MPa	1380 psi	ASTM D-638
Elongation at Yield	255 %	255 %	ASTM D-638
100% Modulus	0.00503 GPa	0.730 ksi	ASTM D-638

Processing Properties	Metric	English	Comments
Melt Temperature	168 °C	335 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China