

Axiall 18901 Wire & Cable Flexible PVC

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Wire and Cable Grade

Material Notes:

General purpose, non-lead stabilized, 105°C rated jacketing compound. Formulated to have good migration resistance and flame retardant

properties.Information provided by Georgia GulfGeorgia Gulf became Axiall Corporation in 2013.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Axiall-18901-Wire-Cable-Flexible-PVC.php

| Physical Properties | Metric | English | Comments |
|---------------------|------------------|------------------|------------|
| Specific Gravity | 1.33 - 1.37 g/cc | 1.33 - 1.37 g/cc | ASTM D-792 |

| Mechanical Properties | Metric | English | Comments |
|-------------------------|------------|----------|----------------------|
| Hardness, Shore A | 87 - 93 | 87 - 93 | delayed; ASTM D-2240 |
| Tensile Strength, Yield | 18.3 MPa | 2650 psi | ASTM D-638 |
| Elongation at Yield | 350 % | 350 % | ASTM D-638 |
| 100% Modulus | 0.0110 GPa | 1.60 ksi | ASTM D-638 |

| Thermal Properties | Metric | English | Comments |
|--------------------|--------|---------|------------|
| Oxygen Index | 25.5 % | 25.5 % | ASTM D-638 |

| Processing Properties | Metric | English | Comments |
|-----------------------|--------|---------|----------|
| Melt Temperature | 185 °C | 365 °F | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China