

Axiall 6680 Rigid PVC, Molding, White 476

Category: Polymer, Thermoplastic, Vinyl (PVC)

Material Notes:

Georgia Gulf 6680 White 476 is a weatherable, high flow injection molding compound, specially formulated for outdoor UV exposure. This compound was designed to be used in various accessory parts, such as fence post caps, rain gutter parts, etc.Information provided by Georgia Gulf Georgia Gulf became Axiall Corporation in 2013.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Axiall-6680-Rigid-PVC-Molding-White-476.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.41 g/cc	1.41 g/cc	ASTM D-792
Linear Mold Shrinkage	0.0030 - 0.0040 cm/cm	0.0030 - 0.0040 in/in	ASTM D-955

Mechanical Properties	Metric	English	Comments	
Hardness, Rockwell R	97	97	ASTM D-785	
Tensile Strength, Yield	40.0 MPa	5800 psi	ASTM D-638	
Tensile Modulus	2.41 GPa	350 ksi	ASTM D-638	
Flexural Strength	65.5 MPa	9500 psi	ASTM D-790	
Flexural Modulus	2.14 GPa	310 ksi	ASTM D-790	
Izod Impact, Notched	9.08 J/cm	17.0 ft-lb/in	ASTM D-256	
	@Thickness 3.17 mm	@Thickness 0.125 in		

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	70.0 °C	158 °F	ASTM D-648
Flammability, UL94	V-0	V-0	
Oxygen Index	35 %	35 %	ASTM D-2863

Descriptive Properties	Value	Comments
Flow Ratio (Distance/Wall Thickness, 390-400°F)	230	Georgia Gulf Test

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com



Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China