

BASF Hexamethylenediamine 70%

Category : Fluid

Material Notes:

Recommended use: For the production of homopolymerisates and copolymerisates, initial product for chemical syntheses
Information provided by BASF

Order this product through the following link:

http://www.lookpolymers.com/polymer_BASF-Hexamethylenediamine-70.php

Physical Properties	Metric	English	Comments
Density	0.920 g/cc @Temperature 40.0 °C	0.0332 lb/in ³ @Temperature 104 °F	
pH	12.4	12.4	100 g/l
Viscosity Measurement	0.90 @Temperature 40.0 °C	0.90 @Temperature 104 °F	[mPa.s] Dynamic
Vapor Pressure	0.0400 bar @Temperature 50.0 °C	30.0 torr @Temperature 122 °F	

Thermal Properties	Metric	English	Comments
Melting Point	5.50 °C	41.9 °F	Solidification
Boiling Point	111.5 °C	232.7 °F	
Flash Point	>= 85.0 °C	>= 185 °F	Directive 92/69/EEC, A.9

Descriptive Properties	Value	Comments
Commercial Status	Europe	
Ignition Temperature	305°C	DIN 51794

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China