

BASF Master Builders Solutions ChemRex® CX-948 Urethane Adhesive/Sealant

Category : Polymer , Adhesive , Thermoset , Polyurethane, TS , Thermoset Polyurethane, Adhesive

Material Notes:

Typical applications include high-solids subfloor adhesive, manufacture of windows, doors, and panels, and the assembly of trucks, cabs, and vans. The working open time is 45-60 minutes. The freeze-thaw stability has unlimited cycles. The flash point is 250°F. The shrinkage is none. Information provided by ChemRex, Inc. Product of former ChemRex, Inc. BASF launched the Master Builders Solutions brand on January 15, 2014.

Order this product through the following link:

http://www.lookpolymers.com/polymer_BASF-Master-Builders-Solutions-ChemRex-CX-948-Urethane-AdhesiveSealant.php

Physical Properties	Metric	English	Comments
Density	1.26 g/cc	0.0455 lb/in ³	
Viscosity	800000 - 1.20e+6 cP	800000 - 1.20e+6 cP	

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	6.41 - 7.25 MPa	930 - 1050 psi	Tensile shear on aluminum to aluminum; 2.17 MPa on metal to douglas fir; 3.72 MPa on OSB (oriented strandboard) to OSB; 6.76 MPa on plywood to treated lumber

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China