

Bostik 2106 Low viscosity, quick grab EVA Glue Stick

Category : Polymer , Adhesive , Thermoplastic , Ethylene Vinyl Acetate , Ethylene Vinyl Acetate Copolymer (EVA), Adhesive/Sealant Grade

Material Notes:

Bostik 2106 Low viscosity, quick grab EVA Glue Stick Low viscosity. Quick grab for woodworking, general assembly and various plastics.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Bostik-2106-Low-viscosity-quick-grab-EVA-Glue-Stick.php

Physical Properties	Metric	English	Comments
Viscosity	3700 cP @Temperature 177 °C	3700 cP @Temperature 350 °F	Typical

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	68.9 °C	156 °F	
Minimum Service Temperature, Air	-17.8 °C	0.000 °F	

Processing Properties	Metric	English	Comments
Pot Life	0.17 - 0.50 min	0.17 - 0.50 min	Open Time

Descriptive Properties	Value	Comments
Color	Tan	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China