

## Cheng Yu Plastic FRCV200 Flame Retardant Nylon 66, 30% Mineral Reinforced

Category : Polymer , Thermoplastic , Nylon , Nylon 66 , Nylon 66, 30% Mineral Filled

Material Notes:

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Cheng-Yu-Plastic-FRCV200-Flame-Retardant-Nylon-66-30-Mineral-Reinforced.php](http://www.lookpolymers.com/polymer_Cheng-Yu-Plastic-FRCV200-Flame-Retardant-Nylon-66-30-Mineral-Reinforced.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.30 g/cc	1.30 g/cc	ASTM D792
Water Absorption	1.0 - 2.0 %	1.0 - 2.0 %	ASTM D570
Linear Mold Shrinkage	0.0020 - 0.020 cm/cm	0.0020 - 0.020 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell M	90	90	ASTM D785
Tensile Strength, Yield	88.3 MPa	12800 psi	ASTM D638
Flexural Yield Strength	137 MPa	19900 psi	ASTM D790
Izod Impact, Notched	0.539 J/cm	1.01 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	255 °C	491 °F	ASTM D648
Flammability, UL94	V-1	V-1	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China