

Cheng Yu Plastic NGCV2 Flame Retardant Nylon 6, 20% Mineral Reinforced

Category : Polymer , Thermoplastic , Nylon , Nylon 6 , Nylon 6, 20% Mineral Filled

Material Notes:

Order this product through the following link:

http://www.lookpolymers.com/polymer_Cheng-Yu-Plastic-NGCV2-Flame-Retardant-Nylon-6-20-Mineral-Reinforced.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.10 g/cc	1.10 g/cc	ASTM D792
Water Absorption	0.20 %	0.20 %	ASTM D570
Linear Mold Shrinkage	0.0080 - 0.015 cm/cm	0.0080 - 0.015 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell M	93	93	ASTM D785
Tensile Strength, Yield	73.5 MPa	10700 psi	ASTM D638
Flexural Yield Strength	123 MPa	17800 psi	ASTM D790
Izod Impact, Notched	0.539 J/cm	1.01 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	230 °C	446 °F	ASTM D648
Flammability, UL94	V-0	V-0	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China