

## Chevron Phillips Ryton® P-4-60 Polyphenylene Sulfide Resin (discontinued \*\*)

Category : Polymer , Thermoplastic , Polyphenylene Sulfide (PPS) , Polyphenylene Sulfide (PPS) Coating Resin

### Material Notes:

Tan Color Polyphenylene Sulfide Resin Ryton® P-4-60 is supplied as pellets. The powder form is P-4. Ryton® PPS exhibits excellent thermal stability and chemical resistance and is suitable for a variety of applications including compounds, coatings, film, and fiber. 0.8 wt % Ash.

Particle size: 95 wt % passing 35 mesh. 90 wt % passing 60 mesh. Data provided by Chevron Phillips Chemical Company LP. Solvay

Specialty Polymers has acquired the Ryton product line. This product was discontinued prior to the acquisition and is listed under the

Chevron Phillips name for historical purposes.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Chevron-Phillips-Ryton-P-4-60-Polyphenylene-Sulfide-Resin-nbspdiscontinued-.php](http://www.lookpolymers.com/polymer_Chevron-Phillips-Ryton-P-4-60-Polyphenylene-Sulfide-Resin-nbspdiscontinued-.php)

Physical Properties	Metric	English	Comments
Melt Flow	75 g/10 min @Load 5.00 kg, Temperature 316 °C	75 g/10 min @Load 11.0 lb, Temperature 601 °F	Procedure B; ASTM D1283

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China