

## Chevron Phillips Ryton® PR27 Polyphenylene Sulfide Resin (discontinued \*\*)

Category: Polymer, Thermoplastic, Polyphenylene Sulfide (PPS), Polyphenylene Sulfide (PPS); Molded

## **Material Notes:**

Characteristics: Excellent thermal stabilityExcellent chemical resistanceApplications: CoatingsCompoundsExtrusionInformation provided by Chevron Phillips.Solvay Specialty Polymers has acquired the Ryton product line. This product was discontinued prior to the acquisition and is listed under the Chevron Phillips name for historical purposes.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Chevron-Phillips-Ryton-PR27-Polyphenylene-Sulfide-Resin-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Particle Mesh Size	35 Mesh	35 Mesh	85 wt% Passing
	60 Mesh	60 Mesh	75 wt% Passing
	500 g/10 min	500 g/10 min	
	300 g/ 10 mm	000 g/ 10 111111	
Melt Flow	@Load 5.00 kg, Temperature 316 °C	@Load 11.0 lb, Temperature 600 °F	ASTM D1283

Descriptive Properties	Value	Comments
Color	Tan	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China