

ChevronTexaco Crater® Fluid H

Category : Fluid , Lubricant

Material Notes:

Texaco Crater lubricants delivers value through:Low environmental impact – Contains a carrier solvent that is a non-ozone depleting diluent.Good water resistance – Strong resistance to water washout.Long equipment life – High film strength provides excellent anti-wear protection.Reduced operating cost – Long lasting lubrication film reduces frequency of repeated application and, therefore, overall quantity of lubricant used.Flexibility to use in wet conditions – Resists rust, supporting longer gear life, and assures good film strength even in a wet environment.Texaco Crater lubricants are formulated with high viscosity mineral oils, tackiness additives, wetting agents and rust inhibitors to protect metal surfaces.Texaco Crater O is a straight mineral oil lubricant.Texaco Crater 2X and 5X are compounded residual oils.Texaco Crater Fluids M and H are compounded with residual oils and a high flash solvent to provide easier applications.They meet the performance requirements of AGMA Lubricants Nos.14R and 15R, respectively.Texaco Crater CSF is a sprayable lithium soap based open gear lubricant which is chlorinated solvent free. Texaco Crater is recommended:for wire ropes, flexible couplingsfor open gears of mine hoistsfor gears and sliding surfaces of drag lines and shovel, ball mills, mixersfor construction and dredging equipmentfor chain and sprocket lubricationas a tenacious fifth wheel lubricantTypical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing.Notes:Minimum operating temperature is the lowest temperature at which a grease, already in place, could be expected to provide lubrication. Most greases cannot be pumped at these minimum temperatures.Maximum operating temperature is the highest temperature at which the grease could be used with frequent (daily) relubrication.Determined on mineral oil extracted by vacuum filtration.CPS Number: 220962; MSDS Number: 9015

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Crater-Fluid-H.php

| Physical Properties | Metric | English | Comments |
|---------------------|----------------------------------|---------------------------------|----------|
| Kinematic Viscosity | 1710 cSt @Temperature 50.0 °C | 1710 cSt @Temperature 122 °F | |

| Thermal Properties | Metric | English | Comments |
|----------------------------------|----------|-----------|-------------|
| Maximum Service Temperature, Air | 60.0 °C | 140 °F | See Note 2. |
| Minimum Service Temperature, Air | -18.0 °C | -0.400 °F | See Note 1. |
| Pour Point | -21.0 °C | -5.80 °F | |
| Flash Point | 116 °C | 241 °F | |

| Descriptive Properties | Value | Comments |
|------------------------|-------------------|----------|
| Color | Black | |
| Contains Diluent4 | YES | |
| Texture | Semi-fluid, Tacky | |

| Thickener Descriptive Properties | Asphaltic Value | Comments |
|-------------------------------------|--------------------|----------|
|-------------------------------------|--------------------|----------|

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China