

ChevronTexaco Gear Compounds EP, ISO 460

Category : Fluid , Lubricant

Material Notes:

FeaturesChevron Gear Compounds EP are multipurpose gear lubricants.They provide good thermal stability, extreme pressure protection, antiwear and demulsibility, oxidation, rust, corrosion control and foam inhibition.Chevron Gear Compounds EP used in misting systems provide excellent oxidation stability to prevent oil mist deposits. They will form a high volume of mist droplets for transmission to the point of application. Chevron Gear Compounds EP have minimal stray mist (fog).ApplicationsChevron Gear Compounds EP are recommended for all industrial enclosed gearing and wherever an AGMA extreme pressure lubricant is specified.Chevron Gear Compounds EP, in the proper viscosity grade, are recommended for all mist oil application systems.The same products can also be used in general industrial plant lubrication where the performance properties of this type of lubricant are required.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Gear-Compounds-EP-ISO-460.php

Physical Properties	Metric	English	Comments
API Gravity	26.1 °	26.1 °	
Viscosity Measurement	95	95	Viscosity Index; ASTM D2270
Saybolt Viscosity at 100°F	2341 SUS	2341 SUS	
Saybolt Viscosity at 210°F	144 SUS	144 SUS	
Kinematic Viscosity at 40°C (104°F)	437 cSt	437 cSt	ASTM D445
Kinematic Viscosity at 100°C (212°F)	29.4 cSt	29.4 cSt	ASTM D445

Mechanical Properties	Metric	English	Comments
Timken Test	29500 g	65.0 lb	

Thermal Properties	Metric	English	Comments
Pour Point	-12.0 °C	10.4 °F	ASTM D97
Flash Point	245 °C	473 °F	ASTM D92

Descriptive Properties	Value	Comments
FZG Gear Wear Test, Failure Load Stage	12	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China