

ChevronTexaco Geotex® HD SAE 40

Category : Fluid , Lubricant

Material Notes:

Texaco Geotex HD is a medium ash, intermediate base number, dispersant/detergent type engine oil. It is manufactured using highly refined paraffinic base oils and an additive package containing ashless dispersant, oxidation inhibitors, metallic detergents, and a metallic antiwear agent. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 221852; MSDS Number: 8627

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Geotex-HD-SAE-40.php

Physical Properties	Metric	English	Comments
API Gravity	29.7 °	29.7 °	
Viscosity Measurement	100	100	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	150 cSt	150 cSt	
Kinematic Viscosity at 100°C (212°F)	15 cSt	15 cSt	
Ash	0.90 %	0.90 %	Sulfated Ash

Thermal Properties	Metric	English	Comments
Pour Point	-15.0 °C	5.00 °F	
Flash Point	259 °C	498 °F	

Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.108 %	0.108 %	
Zinc, Zn	0.12 %	0.12 %	

Chemical Properties	Metric	English	Comments
Acid Value	2.2	2.2	ASTM D 664
Total Base Number	7.6	7.6	ASTM D2896

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China