

ChevronTexaco Havoline® SAE 5W-30 Synthetic Motor Oil

Category : Fluid , Lubricant

Material Notes:

Havoline Synthetic Motor Oil is recommended for all four-stroke gasoline engines used in passenger cars, sport utility vehicles, and light trucks. 5W-30 and 10W-30 meet: API Service Categories SL/CF, SJ/CF, SH, SG, Energy conserving for API SLILSAC GF-3ACEA A1-98General Motors GM 9986125, 9986126, 9986137, 4718MChrysler MS 6395-HFord ESE-M2C 153-GJapanese VTWPeugeot TU 3M Scuff TestDepartment of Defense Commercial Item Description A-A-52309BTypical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 222102; MSDS Number: 8602

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Havoline-SAE-5W-30-Synthetic-Motor-Oil.php

Physical Properties	Metric	English	Comments
API Gravity	31.7 °	31.7 °	
Viscosity	3700 cP	3700 cP	Cold Crank
	@Temperature -30.0 °C	@Temperature -22.0 °F	
Viscosity Measurement	172	172	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	58.1 cSt	58.1 cSt	
Kinematic Viscosity at 100°C (212°F)	10.5 cSt	10.5 cSt	
Ash	0.93 %	0.93 %	Sulfated Ash

Thermal Properties	Metric	English	Comments
Pour Point	-42.0 °C	-43.6 °F	
Flash Point	244 °C	471 °F	

Component Elements Properties	Metric	English	Comments
Phosphorous, P	0.098 %	0.098 %	
Zinc, Zn	0.107 %	0.107 %	

Chemical Properties	Metric	English	Comments
Total Base Number	8.6	8.6	ASTM D2896

Descriptive Properties	Value	Comments
Noack Volatility, wt%	10	250°C, 1 h

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China