

ChevronTexaco Rando® HDZ 32

Category : Fluid , Lubricant

Material Notes:

Texaco Rando HDZ oils deliver value through: High oxidation stability – Longer service life than attainable with conventional lubricants used in high pressure service. Protection against rust and corrosion – Gives excellent protection against corrosion of both copper and steel. Passes ASTM D 665A distilled water rust test and ASTM D 665B salt water rust test. High viscosity index – Minimum change in viscosity over wide operating temperatures. Foam inhibition – Contains special foam suppressant. Eliminate both foaming and aeration problems. Excellent antiwear properties Good stability – in the presence of water in the ASTM D 2619 Hydrolytic Stability Test and in the presence of copper and steel at 135°C (275°F) in the Cincinnati Machine Thermal Stability Test. Fast water separation – Prevents rust problems by fast release of water. Good filterability – Excellent thermal and hydrolytic stability prevents formation of deposits that may interfere with filtration in equipment having close tolerances. Seal conditioning – For longer seal life and leak reduction. Texaco Rando HDZ oils are designed to give maximum protection to hydraulic pumps. They are formulated with antiwear additives, oxidation and corrosion inhibitors, foam and aeration suppressants, and a shear stable viscosity index improver. Hydraulic systems, due to the nature of their operation, experience accelerated wear unless they are protected by clean, high quality antiwear hydraulic oils. Surging pressures in pumps and valves can increase metal-to-metal contact unless antiwear protection is present. The antiwear additives in Texaco Rando HDZ plate out on the metal surfaces. This plating minimizes metal-to-metal contact, which is most severe in vane-, piston-, and gear type pumps. As hydraulic pressures increase over 1000 psi, the need for antiwear protection increases proportionally. Texaco Rando HDZ oils are versatile lubricants available in multiviscosity ISO 15, 22, 32, 46, 68, and 100. The multiviscosity feature allows even and continuous power transmission over a wide temperature range with a minimum of shudder, and increased accuracy. They are recommended for hydraulic or circulating oil systems, including marine on-deck machinery, hydraulic actuated loading bins, or equipment that runs at various operating temperatures. Texaco Rando HDZ ISO 32, 46, and 68 meet all major pump manufacturers requirements including: Vickers I-286-S, M 2950-S, 35VQ 25 Racine Model SC Cincinnati Machine P-68 (ISO 32), P-70 (ISO 46), P-69 (ISO 68) Denison HF-0, HF-2 In a clean, dry environment, Texaco Rando HDZ ISO 15, 22, 32, 46, 68, and 100 typically meet a dielectric strength of 35 kV (ASTM D 877). Texaco Rando HDZ oils meet the requirements (discontinued in 1998) of the U.S. Department of Agriculture (USDA) for use in federally inspected meat and poultry plants as H2 lubricants with no food contact. Do not use in high pressure systems in the vicinity of flames, sparks and hot surfaces. Use only in well ventilated areas. Keep container closed. Typical test data are average values only. Minor variations which do not affect product performance are to be expected in normal manufacturing. CPS Number: 221493; MSDS Number: 8708

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Rando-HDZ-32.php

Physical Properties	Metric	English	Comments
API Gravity	33.1 °	33.1 °	
Viscosity Measurement	155	155	Viscosity Index
Saybolt Viscosity at 100°F	163 SUS	163 SUS	
Saybolt Viscosity at 210°F	47.5 SUS	47.5 SUS	
Kinematic Viscosity at 40°C (104°F)	32 cSt	32 cSt	
Kinematic Viscosity at 100°C (212°F)			

Physical Properties	^{6.4 CSI} Metric	^{6.4 CSI} English	Comments
Oxidative Stability	>= 6000 hour	>= 6000 hour	Hours to 2 mg KOH/g acid number; ASTM D943

Thermal Properties	Metric	English	Comments
Pour Point	-50.0 °C	-58.0 °F	
Flash Point	220 °C	428 °F	

Electrical Properties	Metric	English	Comments
Dielectric Strength	35.0 kV/mm @Thickness 1.00 mm	889 kV/in @Thickness 0.0394 in	ASTM D877

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China