

ChevronTexaco Vistac® ISO 150 Rock Drill Oil

Category : Fluid , Lubricant

Material Notes:

FeaturesChevron Rock Drill Oils Vistac are designed to give maximum protection to percussion rock drills.They are formulated from highly refined, high viscosity index, paraffinic base stocks and additives, which provide all of the performance characteristics, expected of a superior rock drill oil. As indicated by part of the name, Vistac, the additives provide an unusual adhesive or tacky quality.Chevron Rock Drill Oils Vistac are formulated to meet the critical lubrication demands of percussion rock drills. Their superior extreme pressure performance provides protection for the rock drill piston, rifle bar and nut against the heavy shock loads typical of rock drill service. The adhesiveness and emulsification tendency of these oils provide a tenacious lubricant film on the rock drills moving parts which will not be washed off by incidental water that is common in the compressed air which drives the piston in this application.The oils also provide excellent rust and corrosion protection, which is important in light of the corrosive environments in which many rock drills are used. Chevron Rock Drill Oils Vistac contain no chlorinated additives and are completely ashless, minimizing environmental and disposal considerations.Additionally, since rock drills are frequently used in mining environments where ventilation is limited, the low odor and toxicity of these lubricants are added benefits.**Applications**Chevron Rock Drill Oils Vistac have proven excellence in all air-operated tools, such as jackhammers, drifters, etc.The wide viscosity range of this product line makes them suitable for use under many different climatic conditions.The additive package of these oils provides many performance characteristics, which lend themselves well to the lubrication of enclosed gears, and all types of industrial plain and anti-friction bearings.Their tacky quality makes these oils suitable for oncethrough applications; e.g. lubrication of chain drives.They meet the performance requirements of many rock drill manufacturers, such as Ingersoll-Rand, Gardner-Denver, Sullivan, etc.Chevron Rock Drill Oils Vistac ISO 46, 100, 150, 220, and 320 meet all of the specifications of Ingersoll-Rand and Sullivan for light, medium, and heavy rock drill oils.

Order this product through the following link:

http://www.lookpolymers.com/polymer_ChevronTexaco-Vistac-ISO-150-Rock-Drill-Oil.php

| Physical Properties | Metric | English | Comments |
|--------------------------------------|----------|----------|-----------------------------|
| API Gravity | 29.8 ° | 29.8 ° | |
| Viscosity Measurement | 99 | 99 | Viscosity Index; ASTM D2270 |
| Saybolt Viscosity at 100°F | 750 SUS | 750 SUS | |
| Saybolt Viscosity at 210°F | 77 SUS | 77 SUS | |
| Kinematic Viscosity at 40°C (104°F) | 143 cSt | 143 cSt | ASTM D445 |
| Kinematic Viscosity at 100°C (212°F) | 14.4 cSt | 14.4 cSt | ASTM D445 |

| Mechanical Properties | Metric | English | Comments |
|-----------------------|-----------|---------|----------|
| Falex Load Test | 1.59e+6 g | 3500 lb | |
| Timken Test | 24900 g | 55.0 lb | |

| Thermal Properties | Metric | English | Comments |
|--------------------|----------|----------|----------|
| Pour Point | -24.0 °C | -11.2 °F | ASTM D97 |
| Flash Point | 260 °C | 500 °F | ASTM D92 |

| Descriptive Properties | Value | Comments |
|------------------------|-------|----------|
| Steam emulsion number | >1200 | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China