

Colorite Polymers Weatherflex™ CS1525WX (NTL01B) Wire and Cable Vinyl Compound

Category : Polymer , Thermoplastic , Vinyl (PVC) , PVC, Wire and Cable Grade

Material Notes:

Description: Colorite specialty wire and cable compounds feature low smoke properties, excellent flame retardance, low temperature flexibility, and resistance to abrasion and chemicals. All are available in UL and non-UL grades. In addition, the engineering-grade thermoplastic elastomers we offer can stand up to the most demanding applications . . . while providing the most desirable performance characteristics at a cost that's more affordable than "ordinary" elastomers. Typical Applications: Class 36 TPE non-lead jacket for flexible cords. Information provided by Colorite Polymers.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Colorite-Polymers-Weatherflex-CS1525WX-NTL01B-Wire-and-Cable-Vinyl-Compound.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.25 g/cc	1.25 g/cc	ASTM D792
Loss On Ignition	33 %	33 %	ASTM 2863

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	74	74	10 sec; ASTM D2240
Tensile Strength, Ultimate	19.0 MPa	2760 psi	ASTM D412
Elongation at Break	470 %	470 %	ASTM D412

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	105 °C	221 °F	
Brittleness Temperature	-57.0 °C	-70.6 °F	ASTM D746

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China