

## ConocoPhillips HD Fleet Supreme™ 15W-40 Engine Oil

Category : Fluid , Lubricant

### Material Notes:

Description: Conoco HD Fleet Supreme Engine Oil is a high-quality engine oil formulated from Conoco's premium hydrocracked base stock and unique additive technology. It easily satisfies the warranty requirements of most domestic and import manufacturers of diesel and gasoline engines. HD Fleet Supreme meets or exceeds the latest API CH-4 service requirements, Mack EO-M, EO-M Plus, Cummins CES 20071 and 20076 and Volvo VDS specifications. This heavy-duty engine oil is specifically formulated to meet the needs of the new generation low-emissions diesel engines operated on low-sulfur diesel fuel, as well as older diesel engines designed to operate on high-sulfur diesel fuel. HD Fleet Supreme Engine Oil is recommended for on- and off-highway applications in most engines manufactured by Cummins, Detroit Diesel, Caterpillar, Mack, Navistar, John Deere, Komatsu, Saab-Scania, Volvo- GM and others. HD Fleet Supreme Engine Oil is technologically advanced to provide excellent soot control, as well as protect against wear, deposits, rust and corrosion, foaming, and high-temperature oil oxidation and thickening. HD Fleet Supreme Engine Oil is available in two SAE viscosity grades: 15W-40 and 10W-30. Information provided by ConocoPhillips.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ConocoPhillips-HD-Fleet-Supreme-15W-40-Engine-Oil.php](http://www.lookpolymers.com/polymer_ConocoPhillips-HD-Fleet-Supreme-15W-40-Engine-Oil.php)

Physical Properties	Metric	English	Comments
API Gravity	31.3 °	31.3 °	
Viscosity Measurement	140	140	Viscosity Index
Kinematic Viscosity at 40°C (104°F)	116 cSt	116 cSt	
Kinematic Viscosity at 100°C (212°F)	15.4 cSt	15.4 cSt	
Ash	1.2 %	1.2 %	Sulfur
ASTM Color	3.0	3.0	

Thermal Properties	Metric	English	Comments
Pour Point	-37.2 °C	-35.0 °F	
Flash Point	232 °C	450 °F	

Chemical Properties	Metric	English	Comments
Total Base Number	>= 8.2	>= 8.2	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China