

## ConocoPhillips Hydroclear® 250 Industrial Oil

Category : Fluid , Lubricant

**Material Notes:**

Description: Conoco Hydroclear Industrial Oil is a high-quality, general-purpose industrial lubricant formulated from premium Conoco hydrocracked base stocks. Hydroclear Industrial Oil is recommended for use in a variety of applications which require a pure fluid.

Hydroclear Industrial Oil is ideally suited for use as a seal oil, process oil, concrete form oil, deepwell pump drip oil, diluent, extender oil or other similar application. Hydroclear Industrial Oil provides good thermal stability, low volatility and high purity. Hydroclear Industrial Oil is available in seven different viscosity grades to meet the needs of most applications and operating conditions. Information provided by ConocoPhillips.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ConocoPhillips-Hydroclear-250-Industrial-Oil.php](http://www.lookpolymers.com/polymer_ConocoPhillips-Hydroclear-250-Industrial-Oil.php)

Physical Properties	Metric	English	Comments
Density	0.863 g/cc	0.0312 lb/in <sup>3</sup>	
Viscosity Measurement	100	100	Viscosity Index
Saybolt Viscosity at 100°F	244 SUS	244 SUS	
Saybolt Viscosity at 210°F	49 SUS	49 SUS	
Kinematic Viscosity at 40°C (104°F)	47 cSt	47 cSt	
Kinematic Viscosity at 100°C (212°F)	6.9 cSt	6.9 cSt	
ASTM Color	0.50	0.50	

Thermal Properties	Metric	English	Comments
Pour Point	-15.0 °C	5.00 °F	
Flash Point	218 °C	425 °F	

Optical Properties	Metric	English	Comments
Refractive Index	1.4569	1.4569	

Descriptive Properties	Value	Comments
Aniline Point	236°F	
Carbon Residue	0.06	
Characterization D-2007	0.1% Polar	Test inaccurate with HC base oils
	3.4% Aromatics (fully saturated)	Test inaccurate with HC base oils

Descriptive Properties	Value	Comments
Composition, Supercritical Fluid Chromatography	0% Aromatics	Test inaccurate with HC base oils
	0% Polars	
	100% Saturates	
Distillation D-2887 10%	738	
Distillation D-2887 50%	846	
Distillation D-2887 90%	930	
Distillation D-2887 IBP	641	
HPLC Aromatic Detection 1-Ring	330 ppm	
HPLC Aromatic Detection 2.5-Ring	Not Detectable	
HPLC Aromatic Detection 2-Ring	Max 1 ppm	
HPLC Aromatic Detection 3-Ring and Above	Not Detectable	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China