

## ConocoPhillips Hydroclear® 68 Multi-Way Machine Lubricant

Category : Fluid , Lubricant

**Material Notes:**

Description: Conoco Hydroclear Multi-Way Machine Lubricant is a high-quality, heavy-duty circulating machine tool lubricant formulated from premium Conoco hydrocracked base stocks. Hydroclear Multi-Way Machine Lubricant is specially formulated with proprietary additive chemistry containing oiliness and tackiness agents and is recommended for use on the plain bearing slideways of lathes, shapers, grinders, milling machines and other machine tools. Hydroclear Multi-Way Machine Lubricant also can be used effectively on the slideways of saws and carriages found in lumber mills. Hydroclear Multi-Way Machine Lubricant has exceptional stick/slip properties to prevent problems during slow-speed operations. Hydroclear Multi-Way Machine Lubricant provides exceptional control of lubricant runoff, excellent adhesion to horizontal and vertical way surfaces, good rust and corrosion protection and wear protection. Hydroclear Multi-Way Machine Lubricant is available in ISO viscosity grades 68 and 220. Hydroclear Multi-Way Machine Lubricant has been tested and formally approved by Cincinnati Milacron in accordance with its Lubricant Specifications. Information provided by ConocoPhillips.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ConocoPhillips-Hydroclear-68-Multi-Way-Machine-Lubricant.php](http://www.lookpolymers.com/polymer_ConocoPhillips-Hydroclear-68-Multi-Way-Machine-Lubricant.php)

Physical Properties	Metric	English	Comments
Density	0.882 g/cc	0.0319 lb/in <sup>3</sup>	
Viscosity Measurement	110	110	Viscosity Index
Saybolt Viscosity at 100°F	365 SUS	365 SUS	
Saybolt Viscosity at 210°F	58 SUS	58 SUS	
Kinematic Viscosity at 40°C (104°F)	70 cSt	70 cSt	
Kinematic Viscosity at 100°C (212°F)	9.5 cSt	9.5 cSt	
ASTM Color	1.0	1.0	

Thermal Properties	Metric	English	Comments
Pour Point	-15.0 °C	5.00 °F	
Flash Point	232 °C	450 °F	

Descriptive Properties	Value	Comments
Stick/Slip Ratio	0.6	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China