

## ConocoPhillips Inca® 1000 Oil, AGMA No. 8A Comp.

Category : Fluid , Lubricant

**Material Notes:**

Description: Conoco Inca Oil is a high-quality compounded lubricant recommended for use in heavily loaded industrial and automotive worm gears and bearings operating at moderate to high temperatures. Inca Oil is manufactured with high viscosity-index paraffinic base oils. It is compounded with an acidless tallow oil to emulsify with moisture and provide excellent wettability and lubricity to cylinder and valve surfaces in the presence of wet steam or water. It possesses film strength and oiliness characteristics, which makes it an excellent lubricant for worm gear applications. Information provided by ConocoPhillips.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_ConocoPhillips-Inca-1000-Oil-AGMA-No-8A-Comp.php](http://www.lookpolymers.com/polymer_ConocoPhillips-Inca-1000-Oil-AGMA-No-8A-Comp.php)

Physical Properties	Metric	English	Comments
Density	0.917 g/cc	0.0331 lb/in <sup>3</sup>	
Viscosity Measurement	84	84	Viscosity Index
Saybolt Viscosity at 100°F	4632 SUS	4632 SUS	
Saybolt Viscosity at 210°F	215 SUS	215 SUS	
Kinematic Viscosity at 40°C (104°F)	1000 cSt	1000 cSt	
Kinematic Viscosity at 100°C (212°F)	46 cSt	46 cSt	
ASTM Color	6.5	6.5	

Thermal Properties	Metric	English	Comments
Pour Point	10.0 °C	50.0 °F	
Flash Point	316 °C	600 °F	

Descriptive Properties	Value	Comments
Saponification number	11.8	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China